

Superior thermal management allows for maximum PPF output. All aluminum construction provides years of reliable operation. Control your fixture to the exact wattage you need for your particular license or power allotment.



AUROLA

GREENHOUSE LIGHTING

AURORA SPECS

SPECTRUM	GH Spectrum
PPF	≥ 3,000 μmol/s
INPUT POWER	1200W
EFFICACY	≥ 2.5μmol/J
INPUT VOLTAGE	100-277V, & 480V
WEIGHT	40 lbs (Including Drivers)
MAX AMBIENT TEMPERATURE	95°F / 35°C
DIMMING	0-10V / Wireless Controls
BEAM ANGLE	120°
LIFETIME L90	50,000 hours
POWER FACTOR	> 90%
WARRANTY	5 Year Standard

DETAILS

LIGHT BARS	4 Bars
DRIVER	Remote
SPECTRAL BALANCE	Full Spectrum
DAISY CHAIN POWER	Optional
PANGEA READY	Yes
FRAME	Modular

DIMENSIONS

MODEL	X	Y	Z
AURORA	50"	6.5"	1.1"

ELECTRICAL LOAD

SYSTEM WATTS	120V	208V	220V	240V	277V	347V	480V
1200	10.0	5.77	5.45	5.00	4.33	3.46	2.50

GH SPECTRUM

