

The Sunome Lights allows clients to create a custom, made to order grow lighting Package for high PAR level LED applications. A dedicated heat sink for each LED light engine maximizes the thermal management characteristics of the Sunome series.



SUNOME

CANNABIS LIGHTING

SUNOME SPECS

SPECTRUM	GH Spectrum (High Red)
PPF	≥ 2430 μmol/s
INPUT POWER	900W
EFFICACY	≥ 2.7μmol/J
INPUT VOLTAGE	100-277V, & 480V
WEIGHT	29 lbs (Including Drivers)
MAX AMBIENT TEMPERATURE	95°F / 35°C
DIMMING	0-10V / Wireless Controls
BEAM ANGLE	120°
LIFETIME L90	50,000 hours
POWER FACTOR	> 90%
WARRANTY	5 Year Standard

DETAILS

LIGHT BARS	6 Bars
DRIVER	Integrated
SPECTRAL BALANCE	Full Spectrum
DAISY CHAIN POWER	Optional
PANGEA READY	Yes
FRAME	Fixed

DIMENSIONS

MODEL	X	Y	Z
SUNOME	55"	22"	3.7"

ELECTRICAL LOAD

SYSTEM WATTS	120V	208V	220V	240V	277V	347V	480V
900	7.50	4.33	4.09	3.75	3.25	2.59	1.88

GH SPECTRUM

